



SAFETY DATA SHEET

1. Identification

Product identifier **Carquest Glass Cleaner**

Other means of identification


Product code 1045, CRC# 09624
Recommended use Glass cleaner
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Industries, Inc.
Address 885 Louis Dr.
Warminster, PA 18974 US
Telephone
General Information 215-674-4300
Technical Assistance 800-521-3168
Customer Service 800-272-4620
24-Hour Emergency (CHEMTREC) 800-424-9300 (US)
703-527-3887 (International)
Website www.crcindustries.com

2. Hazard(s) identification

Physical hazards	Gases under pressure	Liquefied gas
Health hazards	Reproductive toxicity	Category 2
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 3
	Hazardous to the aquatic environment, long-term hazard	Category 3
OSHA defined hazards	Not classified.	
Label elements		

Signal word

Warning

Hazard statement

Contains gas under pressure; may explode if heated. Suspected of damaging fertility or the unborn child. Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 49°C/120°F. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wear protective gloves/protective clothing/eye protection/face protection. Avoid release to the environment.

Response

If exposed or concerned: Get medical attention.

Storage

Store locked up. Protect from sunlight. Store in a well-ventilated place. Exposure to high temperature may cause can to burst.

Disposal

Dispose of contents/container in accordance with local/regional/national regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

9.7% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 9.7% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Water		7732-18-5	80 - 90
Liquefied Petroleum Gas		68476-86-8	5 - 10
2-Butoxyethanol		111-76-2	1 - 3
Ethanol		64-17-5	1 - 3
Ammonia		7664-41-7	< 1
Methanol		67-56-1	< 0.2

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	If symptoms develop move victim to fresh air. Get medical attention if symptoms persist.
Skin contact	Rinse skin with water/shower. Get medical attention if irritation develops and persists.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Call a POISON CENTER or doctor/physician.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire-fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop the flow of material, if this is without risk. Collect spillage. Prevent entry into waterways, sewer, basements or confined areas. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Should be handled in closed systems, if possible. Pregnant or breastfeeding women must not handle this product. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Avoid release to the environment. Do not empty into drains. For product usage instructions, please see the product label.

Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Contents under pressure. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
2-Butoxyethanol (CAS 111-76-2)	PEL	240 mg/m ³
		50 ppm
Ammonia (CAS 7664-41-7)	PEL	35 mg/m ³
		50 ppm
Ethanol (CAS 64-17-5)	PEL	1900 mg/m ³
		1000 ppm
Methanol (CAS 67-56-1)	PEL	260 mg/m ³
		200 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
2-Butoxyethanol (CAS 111-76-2)	TWA	20 ppm
Ammonia (CAS 7664-41-7)	STEL	35 ppm
	TWA	25 ppm
Ethanol (CAS 64-17-5)	STEL	1000 ppm
Methanol (CAS 67-56-1)	STEL	250 ppm
	TWA	200 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
2-Butoxyethanol (CAS 111-76-2)	TWA	24 mg/m ³
		5 ppm
Ammonia (CAS 7664-41-7)	STEL	27 mg/m ³
		35 ppm
	TWA	18 mg/m ³
Ethanol (CAS 64-17-5)		25 ppm
	TWA	1900 mg/m ³
		1000 ppm
Methanol (CAS 67-56-1)	STEL	325 mg/m ³
		250 ppm
	TWA	260 mg/m ³
		200 ppm

Biological limit values

ACGIH Biological Exposure Indices Components	Value	Determinant	Specimen	Sampling Time
2-Butoxyethanol (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA), with hydrolysis	Creatinine in urine	*
Methanol (CAS 67-56-1)	15 mg/l	Methanol	Urine	*

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

2-Butoxyethanol (CAS 111-76-2)	Can be absorbed through the skin.
Methanol (CAS 67-56-1)	Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

2-Butoxyethanol (CAS 111-76-2)	Skin designation applies.
Methanol (CAS 67-56-1)	Skin designation applies.

US - Tennessee OELs: Skin designation

2-Butoxyethanol (CAS 111-76-2)	Can be absorbed through the skin.
Methanol (CAS 67-56-1)	Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Methanol (CAS 67-56-1)	Can be absorbed through the skin.
------------------------	-----------------------------------

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

2-Butoxyethanol (CAS 111-76-2)	Can be absorbed through the skin.
Methanol (CAS 67-56-1)	Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

2-Butoxyethanol (CAS 111-76-2)	Can be absorbed through the skin.
--------------------------------	-----------------------------------

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear protective gloves such as: Nitrile. Rubber.

Other Wear appropriate chemical resistant clothing.

Respiratory protection

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state	Liquid.
Form	Aerosol.
Color	Clear.
Odor	Ammoniacal.
Odor threshold	Not available.
pH	10.5
Melting point/freezing point	Not available.
Initial boiling point and boiling range	212 °F (100 °C) estimated
Flash point	None (Tag Closed Cup)
Evaporation rate	Slow.

Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	1.3 % estimated
Flammability limit - upper (%)	25 % estimated
Vapor pressure	280.3 hPa estimated
Vapor density	> 1 (air = 1)
Relative density	0.97 estimated
Solubility (water)	Soluble.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	446 °F (230 °C) estimated
Decomposition temperature	Not available.
Viscosity (kinematic)	Not available.
Percent volatile	99.6 % estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Heat, flames and sparks. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Ingestion	Expected to be a low ingestion hazard.
Inhalation	Prolonged inhalation may be harmful.
Skin contact	2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.
Eye contact	Direct contact with eyes may cause temporary irritation.
Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity Expected to be a low hazard for usual industrial or commercial handling by trained personnel.

Product	Species	Test Results
Carquest Glass Cleaner		
Acute		
<i>Dermal</i>		
LD50	Rabbit	14759.4121 mg/kg estimated
<i>Inhalation</i>		
LC50	Rat	7998.0244 mg/l, 4 hours estimated
<i>Oral</i>		
LD50	Rat	14201.8389 mg/kg estimated

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.

Respiratory sensitization	Not available.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	Risk of cancer cannot be excluded with prolonged exposure.
IARC Monographs. Overall Evaluation of Carcinogenicity	
2-Butoxyethanol (CAS 111-76-2)	3 Not classifiable as to carcinogenicity to humans.
Reproductive toxicity	Suspected of damaging fertility or the unborn child.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not classified.
Chronic effects	Prolonged inhalation may be harmful. May be harmful if absorbed through skin. 2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity	Harmful to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected.		
Product		Species	Test Results
Carquest Glass Cleaner			
Aquatic			
Fish	LC50	Fish	6294.9312 mg/l, 96 hours estimated
<i>Acute</i>			
Crustacea	EC50	Daphnia	202.6171 ppm, 48 hours estimated
Components		Species	Test Results
2-Butoxyethanol (CAS 111-76-2)			
Aquatic			
<i>Acute</i>			
Crustacea	EC50	Water flea (Daphnia magna)	1550 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	>= 1000 mg/l, 96 hours
Ammonia (CAS 7664-41-7)			
Aquatic			
Fish	LC50	Chinook salmon (Oncorhynchus tshawytscha)	0.43 - 0.47 mg/l, 96 hours
Ethanol (CAS 64-17-5)			
Aquatic			
<i>Acute</i>			
Algae	EC50	Green algae (Chlorella kessleri)	1450 mg/l
Crustacea	EC50	Water flea (Daphnia magna)	11.2 mg/l, 48 hours 7.7 - 11.2 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	15300 mg/l, 96 hours > 100 mg/l, 96 hours > 100 mg/l, 96 hours
		Rainbow trout,donaldson trout (Oncorhynchus mykiss)	13000 - 15300 mg/l, 96 hours
Methanol (CAS 67-56-1)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	> 10000 mg/l, 48 hours

Components	Species	Test Results
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) > 100 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability	Not available.
Bioaccumulative potential	Not available.
Partition coefficient n-octanol / water (log Kow)	
2-Butoxyethanol	0.81, log Pow
Ethanol	-0.31
Methanol	-0.77
Mobility in soil	No data available.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal of waste from residues / unused products	This product is not a RCRA hazardous waste (See 40 CFR Part 261.20 – 261.33). Empty containers may be recycled. Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all applicable regulations.
Hazardous waste code	Not regulated.
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

UN number	UN1950
UN proper shipping name	Aerosols, non-flammable, Limited Quantity
Transport hazard class(es)	
Class	2.2
Subsidiary risk	-
Label(s)	2.2
Packing group	Not applicable.
Special precautions for user	Not available.
Special provisions	Not available.
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

IATA

UN number	UN1950
UN proper shipping name	Aerosols, non-flammable, Limited Quantity
Transport hazard class(es)	
Class	2.2
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	No.
ERG Code	2L
Special precautions for user	Not available.
Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.

IMDG

UN number	UN1950
UN proper shipping name	AEROSOLS, LIMITED QUANTITY
Transport hazard class(es)	
Class	2
Subsidiary risk	-
Packing group	Not applicable.

Environmental hazards

Marine pollutant No.
EmS Not available.
Special precautions for user Not available.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

2-Butoxyethanol (CAS 111-76-2)

CERCLA Hazardous Substance List (40 CFR 302.4)

2-Butoxyethanol (CAS 111-76-2)

CERCLA Hazardous Substances: Reportable quantity

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

Food and Drug Administration (FDA) Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 Immediate Hazard - No
Hazard categories Delayed Hazard - Yes
Fire Hazard - No
Pressure Hazard - Yes
Reactivity Hazard - No

SARA 302 Extremely hazardous substance No

US state regulations

US. New Jersey Worker and Community Right-to-Know Act

2-Butoxyethanol (CAS 111-76-2)
Ammonia (CAS 7664-41-7)
Ethanol (CAS 64-17-5)
Methanol (CAS 67-56-1)

US. Massachusetts RTK - Substance List

2-Butoxyethanol (CAS 111-76-2)
Ethanol (CAS 64-17-5)

US. Pennsylvania Worker and Community Right-to-Know Law

Ammonia (CAS 7664-41-7)
Methanol (CAS 67-56-1)
2-Butoxyethanol (CAS 111-76-2)
Ethanol (CAS 64-17-5)

US. Rhode Island RTK

2-Butoxyethanol (CAS 111-76-2)
Ammonia (CAS 7664-41-7)
Methanol (CAS 67-56-1)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

1,4-Dioxane (CAS 123-91-1)	Listed: January 1, 1988
Ethylene oxide (CAS 75-21-8)	Listed: July 1, 1987
Methyl isobutyl ketone (CAS 108-10-1)	Listed: November 4, 2011

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Ethylene oxide (CAS 75-21-8)	Listed: August 7, 2009
Methanol (CAS 67-56-1)	Listed: March 16, 2012

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

Ethylene oxide (CAS 75-21-8)	Listed: February 27, 1987
------------------------------	---------------------------

US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

Ethylene oxide (CAS 75-21-8)	Listed: August 7, 2009
------------------------------	------------------------

Volatile organic compounds (VOC) regulations**EPA**

VOC content (40 CFR 51.100(s)) 9.6 %

Consumer products (40 CFR 59, Subpt. C) Compliant

State

Consumer products This product is regulated as a Glass Cleaner (aerosol). This product is compliant for use in all 50 states.

VOC content (CA) 9.6 %

VOC content (OTC) 9.6 %

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	07-24-2014
Prepared by	Allison Cho
Version #	01
Further information	CRC # 411A
HMIS® ratings	Health: 1* Flammability: 0 Physical hazard: 0 Personal protection: B
NFPA ratings	Health: 1 Flammability: 0 Instability: 0

NFPA ratings



Disclaimer

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries.