

## 1 Identification of the substance and manufacturer

Trade name: **GLOSS SAFETY BLUE**  
 Product code: 97400  
 Product category: PC9a Paints and coatings.  
 Manufacturer/Supplier: Lawson Products, Inc.  
 8770 W. Bryn Mawr Avenue  
 Chicago, IL 60631  
 USA  
 phone: 773-304-5050  
 888-426-4851



Emergency telephone number:

## 2 Hazard(s) identification

### Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.  
 Press. Gas H280 Contains gas under pressure; may explode if heated.  
 Carc. 2 H351 Suspected of causing cancer.  
 Eye Irrit. 2A H319 Causes serious eye irritation.  
 STOT SE 3 H336 May cause drowsiness or dizziness.

### GHS Hazard pictograms



GHS02 GHS04 GHS07 GHS08

### Signal word Hazard statements

Danger  
 Extremely flammable aerosol.  
 Contains gas under pressure; may explode if heated.  
 Causes serious eye irritation.  
 Suspected of causing cancer.  
 May cause drowsiness or dizziness.

### Precautionary statements

If medical advice is needed, have product container or label at hand.  
 Keep out of reach of children.  
 Read label before use.  
 Obtain special instructions before use.  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
 Do not spray on an open flame or other ignition source.  
 Pressurized container: Do not pierce or burn, even after use.  
 Wash hands thoroughly after handling.  
 Use only outdoors or in a well-ventilated area.  
 Do not handle until all safety precautions have been read and understood.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 Avoid breathing dust/fume/gas/mist/vapours/spray.  
 Use personal protective equipment as required.  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 IF exposed or concerned: Get medical advice/attention.  
 If eye irritation persists: Get medical advice/attention.  
 Store locked up.  
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
 Store in a well-ventilated place. Keep container tightly closed.  
 Dispose of contents/container in accordance with local/regional/national/international regulations.

## 3 Composition/information on ingredients

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

### Dangerous components:

67-64-1	Acetone	20.88%
74-98-6	propane	15.83%
106-97-8	n-butane	9.3%
7727-43-7	barium sulphate, natural	8.8%
108-10-1	methyl isobutyl ketone	5.88%
2807-30-9	Glycol Ether EP	5.63%
107-87-9	Methyl Propyl Ketone	3.01%
1330-20-7	xylene (mix)	2.61%
13463-67-7	titanium dioxide	2.54%
110-19-0	isobutyl acetate	2.3%
108-65-6	PM acetate	1.11%

### First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.  
 After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.  
 After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

Trade name: GLOSS SAFETY BLUE

After swallowing: Rinse out mouth and then drink plenty of water.  
Rinse mouth with water. Do not induce vomiting.

(Contd. of page 1)

Most important symptoms and effects: Dizziness

Indication of any immediate medical attention needed: No further relevant information available.

### 5 Fire-fighting measures

Extinguishing agents: CO<sub>2</sub>, sand, extinguishing powder, or water spray. Fight larger fires with water spray or alcohol resistant foam.

Special hazards: CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray.  
Protective equipment for firefighters: Can form explosive gas-air mixtures.

A respiratory protective device may be necessary.

### 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures: Wear protective equipment. Keep unprotected persons away.  
Use respiratory protective device against the effects of fumes/dust/aerosol.

Methods and material for containment and cleaning up: Absorb liquid components with liquid-binding material.

### 7 Handling and storage

Precautions for safe handling: Use only in well ventilated areas.  
Storage requirements: Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.  
Store locked up.

### 8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:	
<b>67-64-1 Acetone</b>	
PEL (USA)	Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm
REL (USA)	Long-term value: 590 mg/m <sup>3</sup> , 250 ppm
TLV (USA)	Short-term value: (1782) NIC-1187 mg/m <sup>3</sup> , (750) NIC-500 ppm Long-term value: (1188) NIC-594 mg/m <sup>3</sup> , (500) NIC-250 ppm BEI
<b>74-98-6 propane</b>	
PEL (USA)	Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm
REL (USA)	Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm
TLV (USA)	refer to Appendix F
<b>106-97-8 n-butane</b>	
REL (USA)	Long-term value: 1900 mg/m <sup>3</sup> , 800 ppm
TLV (USA)	Short-term value: 2370 mg/m <sup>3</sup> , 1000 ppm
<b>7727-43-7 barium sulphate, natural</b>	
PEL (USA)	Long-term value: 15* 5** mg/m <sup>3</sup> *total dust **respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m <sup>3</sup> *total dust **respirable fraction
TLV (USA)	Long-term value: 5* mg/m <sup>3</sup> *inhalable fraction; E
<b>108-10-1 methyl isobutyl ketone</b>	
PEL (USA)	Long-term value: 410 mg/m <sup>3</sup> , 100 ppm
REL (USA)	Short-term value: 300 mg/m <sup>3</sup> , 75 ppm Long-term value: 205 mg/m <sup>3</sup> , 50 ppm
TLV (USA)	Short-term value: 307 mg/m <sup>3</sup> , 75 ppm Long-term value: 82 mg/m <sup>3</sup> , 20 ppm BEI
<b>107-87-9 Methyl Propyl Ketone</b>	
PEL (USA)	Long-term value: 700 mg/m <sup>3</sup> , 200 ppm
REL (USA)	Long-term value: 530 mg/m <sup>3</sup> , 150 ppm
TLV (USA)	Short-term value: 529 mg/m <sup>3</sup> , 150 ppm
<b>1330-20-7 xylene (mix)</b>	
PEL (USA)	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm

(Contd. on page 3)

Trade name: GLOSS SAFETY BLUE

(Contd. of page 2)

REL (USA)	Short-term value: 655 mg/m <sup>3</sup> , 150 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
LV (USA)	Short-term value: 651 mg/m <sup>3</sup> , 150 ppm Long-term value: 434 mg/m <sup>3</sup> , 100 ppm BEI
<b>110-19-0 isobutyl acetate</b>	
REL (USA)	Long-term value: 700 mg/m <sup>3</sup> , 150 ppm
REL (USA)	Long-term value: 700 mg/m <sup>3</sup> , 150 ppm
TLV (USA)	Long-term value: 713 mg/m <sup>3</sup> , 150 ppm
<b>108-65-6 PM acetate</b>	
WEEL (USA)	Long-term value: 50 ppm
<b>Ingredients with biological limit values:</b>	
<b>67-64-1 Acetone</b>	
BEI (USA)	50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
<b>108-10-1 methyl isobutyl ketone</b>	
BEI (USA)	1 mg/L Medium: urine Time: end of shift Parameter: MIBK
<b>1330-20-7 xylene (mix)</b>	
BEI (USA)	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids

**Hygienic protection:** Keep away from foodstuffs and animal feed. Wash hands after use. Immediately remove all soiled and contaminated clothing. Wash hands after use. Avoid contact with the eyes and skin. Do not eat or drink while working.

**Breathing equipment:** A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

**Hand protection:** Protective gloves. The glove material must be impermeable and resistant to the substance.

**Eye protection:** Tightly sealed goggles

**9 Physical and chemical properties**

**Appearance:** Aerosol.  
**Odor:** Aromatic  
**Odor threshold:** Not determined.  
**pH-value:** Not determined.  
**Melting point/Melting range** Undetermined.  
**Boiling point:** -44 °C (-47 °F)  
**Flash point:** -19 °C (-2 °F)  
**Flammability (solid, gas):** Extremely flammable.  
**Decomposition temperature:** Not determined.  
**Auto Igniting:** Product is not self-igniting.  
**Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.  
**Lower Explosion Limit:** 1.7 Vol %  
**Upper Explosion Limit:** 10.9 Vol %  
**Vapor pressure:** Not determined.  
**Relative Density:** Between 0.77 and 0.85 (Water equals 1.00)  
**Vapour density** Not determined.  
**Evaporation rate** Not applicable.  
**Partition coefficient: n-octanol/water:** Not determined.  
**Solubility:** Not determined.  
**Viscosity:** Not determined.  
**VOC content:** 501.6 g/l / 4.19 lb/gl  
**VOC content (less exempt solvents):** 46.6 %  
**MIR Value:** 1.13  
**Solids content:** 32.0 %

**10 Stability and reactivity**

**Reactivity:** Stable at normal temperatures.

Trade name: GLOSS SAFETY BLUE

<p><b>Conditions to avoid:</b></p> <p><b>Chemical stability:</b></p> <p><b>Possibility of hazardous reactions:</b></p> <p><b>Incompatible materials:</b></p> <p><b>Hazardous decomposition:</b></p>	<p>Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.</p> <p>Not fully evaluated.</p> <p>No dangerous reactions known.</p> <p>No further relevant information available.</p> <p>No dangerous decomposition products known.</p>	<p>(Contd. of page 3)</p>
---	--	---------------------------

**11 Toxicological information**

<b>LD/LC50 values that are relevant for classification:</b>		
<b>106-97-8 n-butane</b>		
Inhalative	LC50/4 h	658 mg/l (rat)
<b>108-10-1 methyl isobutyl ketone</b>		
Oral	LD50	2100 mg/kg (rat)
Dermal	LD50	16000 mg/kg (rab)
Inhalative	LC50/4 h	8.3-16.6 mg/l (rat)
<b>1330-20-7 xylene (mix)</b>		
Oral	LD50	8700 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rbt)
Inhalative	LC50/4 h	6350 mg/l (rat)
<b>13463-67-7 titanium dioxide</b>		
Oral	LD50	>20000 mg/kg (rat)
Dermal	LD50	>10000 mg/kg (rbt)
Inhalative	LC50/4 h	>6.82 mg/l (rat)
<b>110-19-0 isobutyl acetate</b>		
Oral	LD50	4763 mg/kg (rbt)
<b>108-65-6 PM acetate</b>		
Oral	LD50	8500 mg/kg (rat)
Inhalative	LC50/4 h	35.7 mg/l (rat)

**Information on toxicological effects:** No data available.  
**Sensitization:** No sensitizing effects known.

**Carcinogenic categories**

<b>IARC (International Agency for Research on Cancer)</b>		
108-10-1	methyl isobutyl ketone	2B
1330-20-7	xylene (mix)	3
13463-67-7	titanium dioxide	2B

**NTP (National Toxicology Program)**

None of the ingredients is listed.

**OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

**12 Ecological information**

<p><b>Aquatic toxicity:</b></p> <p><b>Persistence and degradability:</b></p> <p><b>Bioaccumulative potential:</b></p> <p><b>Mobility in soil:</b></p> <p><b>Other adverse effects:</b></p>	<p>Hazardous for water, do not empty into drains.</p> <p>The product is degradable after prolonged exposure to natural weathering processes.</p> <p>No further relevant information available.</p> <p>No further relevant information available.</p> <p>No further relevant information available.</p>
--	--

**13 Disposal considerations**

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

**Recommendation:** Completely empty cans should be recycled.

**14 Transport information**

<b>UN-Number</b>	UN1950
<b>DOT</b>	Aerosols, flammable
<b>ADR</b>	1950 Aerosols
<b>Transport hazard class(es):</b>	
<b>Class</b>	2.1
<b>Marine pollutant:</b>	No
<b>Special precautions for user:</b>	Warning: Gases
<b>EMS Number:</b>	F-D,S-U
<b>Packaging Group:</b>	--

Trade name: GLOSS SAFETY BLUE

(Contd. of page 4)

UN "Model Regulation": UN1950, Aerosols, 2.1

**15 Regulatory information**

<b>SARA Section 355 (extremely hazardous substances):</b>		
None of the ingredients in this product are listed.		
<b>SARA Section 313 (Specific toxic chemical listings):</b>		
7727-43-7	barium sulphate, natural	
108-10-1	methyl isobutyl ketone	
1330-20-7	xylene (mix)	
<b>CPSC:</b> This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.		
<b>California Proposition 65 chemicals known to cause cancer:</b>		
108-10-1	methyl isobutyl ketone	
13463-67-7	titanium dioxide	
100-41-4	ethyl benzene	
<b>EPA:</b>		
67-64-1	Acetone	I
7727-43-7	barium sulphate, natural	D, CBD(inh), NL(oral)
108-10-1	methyl isobutyl ketone	I
1330-20-7	xylene (mix)	I
110-19-0	isobutyl acetate	D

**16 Other information**

Contact: Regulatory Affairs