



SAFETY DATA SHEET

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier

WAX AND GREASE REMOVER

Other means of identification

Product code 36-700
Recommended use Solvent

Manufacturer/Importer/Supplier/Distributor information

Company name NATIONAL COATINGS & SUPPLIES
Address 4900 FALLS OF NEUSE ROAD, SUITE
150 RALEIGH, NC 27609

Telephone 866-529-1682

Website www.nationalcoatingsandsupplies.com

Emergency phone number EMERGENCY 24 Hrs. 800-424-9300 ChemTrec

SECTION 2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

GHS Classification:

Flammable Liquids, Category 2

Eye Irritation, Category 2B

Skin Irritation, Category 2

Acute toxicity, Inhalation Category 4

GHS Labeling



Symbol:

Signal Word: Danger

Hazard Statements:

Causes eye and skin irritation

Highly flammable liquid and vapor

Harmful if inhaled

Precautionary Statements:

Prevention:

Keep away from flames and hot surfaces. No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion proof electrical equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wear protective gloves/protective clothing/eye protection/face protection.

Wash hands thoroughly after handling.

Avoid breathing mist/vapors/spray.

Use only outdoors or in a well-ventilated area

Response:

In case of fire use dry chemical, alcohol foam, or carbon dioxide to extinguish.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Safety Data Sheet

IF ON SKIN (or hair): Take off immediately all contaminated clothing and wash before use. Rinse skin with water/shower.

If on skin: Wash with plenty of water.

If skin irritation occurs: Get medical advice/attention.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

Call a poison center if you feel unwell.

Storage:

Store in a well-ventilated place. Keep cool.

Disposal:

Dispose contents/container to an approved waste disposal plant.

Potential Health Effects: See Section 11 for more information

This product does not contain carcinogens or potential carcinogens as listed by IARC, NTP, or ACGIH.

This material contains components that are considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Potential Environmental Effects: See Section 12 for more information.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

No.	Component CAS REG. NO.	Amount %	OSHA		ACGIH	
			TWA	STEL	TWA	STEL
1	Isopropyl Alcohol CAS #67-63-0	1-100	400 ppm	Not Avail	400 ppm	Not Avail
2	Xylene CAS #1330-20-7	1-100	100 ppm	150 ppm	100 ppm	150 ppm
3	Light Hydrotreated Distillate 68410-97-9	1-100	5 mg/m ³	Not avail	5 mg/m ³	Not avail

SECTION 4. FIRST AID MEASURES

Emergency first aid procedures by route of exposure:

Inhalation: If overcome by exposure, remove victim to fresh air immediately. Give oxygen or artificial respiration as needed. Obtain medical attention.

Ingestion: Do not induce vomiting. Obtain medical attention.

Skin: Remove contaminated clothing as needed. Wash skin thoroughly with mild soap and water. Flush with lukewarm water for 15 minutes. Seek medical attention.

Eyes: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention.

SECTION 5. FIREFIGHTING MEASURES

Flash Point Light Hydrotreated Distillate: >50°F (> 10°C) Tag Closed Cup

LEL: Not Available

UEL: Not Available

Auto Ignition Temperature: Not Available

Suitable Extinguishing Media:

Water spray, dry chemical, carbon dioxide, alcohol foam

Safety Data Sheet

Products of Combustion:

Carbon dioxide, carbon monoxide

Fire Fighting Equipment/Instructions:

Wear self-contained breathing apparatus and protective clothing. Use water spray to keep fire-exposed containers cool.

HAZARD	HMIS	NFPA
Toxicity	2	2
Fire	3	3
Reactivity	0	0

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Protection: Use personal protective equipment. Ensure adequate ventilation. Eliminate all sources of ignition.

Environmental Precautions: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

Method for Containment: Absorb spilled liquid in suitable non-flammable inert material such as clay, vermiculite or diatomaceous earth.

Methods for Clean-up: Use clean non-sparking tools to collect absorbed material. Dike large spills and place materials in salvage containers.

SECTION 7. HANDLING AND STORAGE

Handling: Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Keep container closed. Wash thoroughly after handling.

Special Handling Statements: Provide good ventilation of working area (local exhaust ventilation if necessary). During processing and handling of the product, comply with the indicative occupational exposure limit values.

Storage: Store in a cool, dry, well ventilated place and keep container tightly closed. Observe the general rules of industrial fire protection.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

Personal Protective Equipment (PPE)

Respiratory Protection: A respiratory protection program that meets OSHA's 29CFR 1910.134 or ANSI Z88.2 requirements must be followed whenever workplace conditions warrant respirator use.

Eye/Face Protection: Eye protection such as chemical splash goggles and/or face shield must be worn.

Hand Protection: Wear chemical resistant gloves such as Butyl rubber or Viton.

Body: When skin contact is possible, protective clothing including apron, sleeves, boots, head and face protection should be worn.

Other Protective Equipment:

Facilities storing or utilizing this material should be equipped with eyewash and/or shower facilities.

Safety Data Sheet

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance, State: Clear Liquid	Regulatory VOC (lbs/gal)	6.37
Color: Pale straw to light amber	Regulatory VOC (g/l)	763.50
Odor: Hydrocarbon, fatty detergent odor	Actual VOC (lbs/gal)	6.37
pH: 6.5 - 8.5	Actual VOC (g/l)	763.50
Vapor Density: Not Available		
Boiling Point: Not Available		
Vapor Pressure: Not Available		
Freezing point: Not Available		
Flash Point (See Section 5)		
Flammability Properties (See section 5)		
Solubility: Not Available		
Specific Gravity: Not Available		
Evaporation Rate: Not Available		
Octanol/Water partition coefficient (Kow): Not Available		
Auto-ignition temperature (See section 5)		
Decomposition temperature: Not Available		
Viscosity: Not Available		

SECTION 10. STABILITY AND REACTIVITY

Stability: This material is considered stable at ambient temperatures 70°C (21°C).

Condition to Avoid: Strong oxidizing agents, heat, flames, sparks, acids, alkalis.

Hazardous Decomposition: Carbon dioxide and carbon monoxide may form when heated to decomposition. **Hazardous Reactions:** This product will not undergo polymerization.

SECTION 11. TOXICOLOGICAL INFORMATION

ACUTE EFFECTS:

Component Analysis LDSO

Isopropyl Alcohol (67-63-0) Inhalation
LC50 Rat: 72.6 mg/L/4H
Oral LD50 Rat: 4396 mg/kg
Dermal LD50 Rat: 12800 mg/kg
Dermal LD50 Rabbit: 12870 mg/kg

Xylene (1330-20-7)

Inhalation LC50 Rat 5000 ppm 4 h;
Inhalation LC50 Rat 47635 mg/L 4 h;
Oral LD50 Rat 4300 mg/kg;
Dermal LD50 Rabbit >1700 mg/kg

CHRONIC EFFECTS:

Component

Light Hydrotreated Distillate (CAS #68410-97-9)

Carcinogenic Effects: Not Available

Mutagenic Effects: Not Available

Teratogenic Effects: Not Available

Developmental Toxicity: Not Available

Safety Data Sheet

Target Organs: Routes of exposure Inhalation. Ingestion. **Eyes** Avoid contact with eyes. Causes eye irritation. **Skin** Avoid contact with the skin. Contact with skin may cause irritation. **Inhalation** Prolonged inhalation may be harmful.

Isopropyl Alcohol (67-63-0)

Carcinogenicity: No known hazards

Mutagenicity: Not available.

Reproductive: Not available.

Developmental: Not available.

Target Organs: skin, eyes, CNS, and respiratory system. **Eye:** Contact with eyes may cause redness and pain. **Skin:** Contact with skin may cause dry skin. **Inhalation:** Inhalation of this material may cause: cough, dizziness, drowsiness, headache, sore throat, abdominal pain, labored breathing, nausea, vomiting, and unconsciousness. **Ingestion:** Ingestion of this material may cause: cough, dizziness, drowsiness, headache, sore throat, abdominal pain, labored breathing, nausea, vomiting, and unconsciousness.

Xylene (1330-20-7)

Carcinogenic Effects: A4 - Not classifiable for human or animal by ACGIH, IARC, or OSHA.

Mutagenic Effects: Xylenes have not demonstrated genotoxic activity in animals or humans and do not appear to be immunotoxic.

Teratogenic Effects: Not Available

Developmental Toxicity: Not Available

Target Organs: Nervous system, respiratory system. From the animal and human toxicology data, xylenes can be characterized as neurotoxic chemicals at moderate to high doses inducing symptoms in humans of dizziness, headache, nausea, and neuromuscular effects, speech impairment, and amnesia at high doses. Aspiration into the lungs of even a small amount may cause severe injury, since its low viscosity and surface tension will cause it to spread over a large surface of pulmonary tissue. Aspiration into the lungs of even a small amount may cause severe injury, since its low viscosity and surface tension will cause it to spread over a large surface of pulmonary tissue. **Eyes:** Irritation from vapors. Splash accidents have produced transient, superficial injury to the eye. **Skin:** May cause skin irritation. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. **Inhalation** Central nervous system depression, narcosis, respiratory tract irritation & pulmonary edema. Severe exposure may cause death. **Ingestion** Aspiration hazard if swallowed. Can enter lungs and cause damage. May be fatal if swallowed. Central nervous system depression, a burning sensation in the oropharynx and stomach. Vomiting. **Potential Chronic Health Effects** Effects of chronic exposure to xylene are similar to those of acute exposure, particularly central nervous system effects (based on animal studies). **Overexposure/Signs/Symptoms:** Headache, tremors, apprehension, memory loss, weakness, dizziness, loss of appetite, nausea, ringing in the ears, irritability, thirst, anemia, mucosal bleeding, enlarged liver, and hyperplasia are reported when chronic inhalation of xylenes has occurred. Repeated contact with the skin can cause defatting dermatitis. Reversible eye damage, including vacuoles in the cornea and conjunctiva, has occurred with chronic xylene exposure.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity: Isopropyl Alcohol (67-63-0)

96 Hr EC50 Scenedesmus Subspicatus: >1000 mg/L

72 Hr EC50 Scenedesmus subspicatus:>1000 mg/L

96 Hr LC50 Pimephales promelas: 9640 mg/L [flow through]

96 Hr LC50 Pimephales promelas: 94900 mg/L [flow through] (29 days old)

96 Hr LC50 Pimephales promelas: 61200 mg/L [flow through] (31 days old)

5 min EC50 Photobacterium phosphoreum: 35390 mg/L

48 Hr EC50 Daphnia magna: 13299 mg/L

Ecotoxicity: Xylene (1330-20-7)

96 Hr LC50 Pimephales promelas: 13.4 mg/L [flow-through];

96 Hr LC50 Oncorhynchus mykiss: 2.661-4.093 mg/L [static];

96 Hr LC50 Oncorhynchus mykiss: 13.5-17.3 mg/L;

96 Hr LC50 Lepomis macrochirus: 13.1-16.5 mg/L [flow -through];

Safety Data Sheet

96 Hr LC50 Lepomis macrochirus: 19mg/L;
96 Hr LC50 Lepomis macrochirus: 7.711- 9.591 mg/L [static];
96 Hr LC50 Pimephales promelas: 23.53-29.97 mg/L [static];
96 Hr LC50 Cyprinus carpio: 780 mg/L [semi-static];
96 Hr LC50 Cyprinus carpio: >780 mg/L;
96 Hr LC50 Poecilia reticulata: 30.26-40.75 mg/L [static]
48 Hr EC50 water flea: 3.82 mg/L;
48 Hr LC50 Gammarus lacustris: 0.6 mg/L
48 Hr EC50 water flea: 3.82 mg/L;
48 Hr LC50 Gammarus lacustris: 0.6 mg/L

SECTION 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with local, state, and federal regulations.

SECTION 14. TRANSPORT INFORMATION

Proper Shipping Name: Paint related material
Hazard Class: 3
Identification No.: UN1263
Packing Group: II
Label: Flammable

SECTION 15. REGULATORY INFORMATION

TSCA Inventory This product and/or its components are listed on the Toxic Substances Control Act (TSCA) inventory.

SARA 302/304 The Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires facilities subject to Subparts 302 and 304 to submit emergency planning and notification information based on Threshold Planning Quantities (TPQs) and Reportable Quantities (RQs) for "Extremely Hazardous Substances" listed in 40 CFR 302.4 and 40 CFR 355. No components were identified.

SARA 313: Xylene [CAS No.: 1330-20-7]

CERCLA The Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) requires notification of the National Response Center concerning release of quantities of "hazardous substances" equal to or greater than the reportable quantities (RQ's) listed in 40 CFR 302.4. As defined by CERCLA, the term "hazardous substance" does not include petroleum, including crude oil or any fraction thereof which is not otherwise specifically designated in 40 CFR 302.4. Chemical substances present in this product or refinery stream that may be subject to this statute are: Xylene [CAS No.: 1330-20-7] RQ = 100 lbs (45.3 kg)

SARA 311/312 Hazard The Superfund Amendments and Reauthorization Act of 1986 (SARA) Title 111 requires facilities subject to this subpart to submit aggregate information on chemicals by "Hazard Category" as defined in 40 CFR 370.2. This material would be classified under the following hazard categories: Acute, Chronic, Fire

SECTION 16. OTHER INFORMATION

Version 2.0
Revision Date 12/07/2016

DISCLAIMER The information accumulated is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made become available subsequently to the date hereof, we do not assume any responsibility for the results of its use. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.