

**SAFETY DATA SHEET**

Revision Date: 08/31/2018

Print Date: 2/17/2020

SDS Number: R0321370

Version: 1.4

ZEREX™ G05@ 50/50 Antifreeze Coolant

ZXG05RU2

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**Product identifier**Trade name : ZEREX™ G05@ 50/50
Antifreeze Coolant**Details of the supplier of the safety data sheet**Valvoline LLC
100 Valvoline Way
Lexington, KY 40509
United States of America (USA)
1-800-TEAMVAL (1-800-832-6825)

SDS@valvoline.com

Emergency telephone number

1-800-VALVOLINE (1-800-825-8654)

Regulatory Information Number

1-800-TEAMVAL (1-800-832-6825)

Product Information

1-800-TEAMVAL (1-800-832-6825)


SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**Acute toxicity (Oral) : Category 4
Carcinogenicity : Category 1B
Reproductive toxicity : Category 1B
Specific target organ systemic toxicity - repeated exposure (Oral) : Category 2 (Kidney, Liver)**GHS label elements**

Hazard pictograms :



Signal Word : Danger

Hazard Statements : Harmful if swallowed.
May cause cancer.
May damage fertility or the unborn child.
May cause damage to organs (Kidney, Liver) through

		Page: 2
SAFETY DATA SHEET		Revision Date: 08/31/2018
		Print Date: 2/17/2020
		SDS Number: R0321370
ZEREX™ G05® 50/50 Antifreeze Coolant		Version: 1.4
ZXG05RU2		

prolonged or repeated exposure if swallowed.

Precautionary Statements : **Prevention:**
 Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
 Wash skin thoroughly after handling.
 Do not eat, drink or smoke when using this product.
 Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.
 IF exposed or concerned: Get medical advice/ attention.
Storage:
 Store locked up.
Disposal:
 Dispose of contents/ container to an approved waste disposal plant.

Other hazards
 None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
ETHYLENE GLYCOL	107-21-1	Acute Tox. 4; H302 STOT RE 2; H373	>=50.00 - < 60.00
DIETHYLENE GLYCOL	111-46-6	Acute Tox. 4; H302 STOT RE 2; H373	>=1.50 - < 5.00
SODIUM BENZOATE	532-32-1	Eye Irrit. 2A; H319	>=1.00 - < 1.50
DISODIUM TETRABORATE	1330-43-4	Repr. 1B; H360	>=0.50 - < 1.00
SODIUM NITRITE	7632-00-0	Ox. Sol. 2; H272 Acute Tox. 3; H301	>=0.10 - < 0.50



SAFETY DATA SHEET

Revision Date: 08/31/2018

Print Date: 2/17/2020

SDS Number: R0321370

ZEREX™ G05@ 50/50 Antifreeze Coolant


Version: 1.4

ZXG05RU2

		Eye Irrit. 2A; H319 Carc. 1B; H350	
SODIUM NITRATE	7631-99-4	Ox. Sol. 3; H272 Eye Irrit. 2A; H319 Carc. 1B; H350	>=0.10 - < 0.50

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
If eye irritation persists, consult a specialist.
- If swallowed : Obtain medical attention.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Effects of acute ethylene glycol poisoning appear in three fairly distinct stages. The initial stage occurs shortly after exposure, lasts 6-12 hours, and is characterized by central nervous system effects (transient exhilaration, nausea, vomiting, and in severe cases, coma, convulsions, and possible death). The second stage lasts from 12-36 hours after exposure and is initiated by the onset of coma. This phase is characterized by tachypnea, tachycardia, mild pulmonary edema, bronchopneumonia, cardiac enlargement, and congestive failure. The final stage occurs 24-72 post-

		Page: 4
SAFETY DATA SHEET		Revision Date: 08/31/2018
		Print Date: 2/17/2020
		SDS Number: R0321370
ZEREX™ G05® 50/50 Antifreeze Coolant		Version: 1.4
ZXG05RU2		

exposure and is characterized by renal failure, ranging from a mild increase in blood urea nitrogen and creatinine followed by recovery, to complete anuria with acute tubular necrosis that can lead to death. Oxaluria is found in most cases. The most significant laboratory finding in ethylene glycol intoxication is severe metabolic acidosis.

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:


- stomach or intestinal upset (nausea, vomiting, diarrhea)
- irritation (nose, throat, airways)
- Cough
- pain in the abdomen and lower back
- cyanosis (causes blue coloring of the skin and nails from lack of oxygen)
- lung edema (fluid buildup in the lung tissue)
- acute kidney failure (sudden slowing or stopping of urine production)
- Convulsions
- Harmful if swallowed.
- May cause cancer.
- May damage fertility or the unborn child.
- May cause damage to organs through prolonged or repeated exposure if swallowed.

Notes to physician

- : This product contains ethylene glycol. Ethanol decreases the metabolism of ethylene glycol to toxic metabolites. Ethanol should be administered as soon as possible in cases of severe poisoning since the elimination half-life of ethylene glycol is 3 hours. If medical care will be delayed several hours, give the patient three to four 1-ounce oral "shots" of 86-proof or higher whiskey before or during transport to the hospital. Fomepizole (4-methylpyrazole) is an effective antagonist of alcohol dehydrogenase, and as such, may be used as an antidote in the treatment of ethylene glycol poisoning. Hemodialysis effectively removes ethylene glycol and its metabolites from the body.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing : High volume water jet

		Page: 5
SAFETY DATA SHEET		Revision Date: 08/31/2018
		Print Date: 2/17/2020
		SDS Number: R0321370
ZEREX™ G05® 50/50 Antifreeze Coolant		Version: 1.4
ZXG05RU2		

media

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Alcohols
Aldehydes
carbon dioxide and carbon monoxide
ethers
toxic fumes
Hydrocarbons
Sodium oxides

Specific extinguishing methods :

Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.


Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapours/dust.
Do not smoke.
Container hazardous when empty.
Avoid exposure - obtain special instructions before use.

		Page: 6
SAFETY DATA SHEET		Revision Date: 08/31/2018
		Print Date: 2/17/2020
		SDS Number: R0321370
ZEREX™ G05® 50/50 Antifreeze Coolant		Version: 1.4
ZXG05RU2		

Avoid contact with skin and eyes.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Observe label precautions.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ETHYLENE GLYCOL	107-21-1	C	50 ppm 125 mg/m3	OSHA P0
		C	40 ppm 100 mg/m3 Vapour	CAL PEL
		TWA	25 ppm Vapour	ACGIH
		STEL	50 ppm Vapour	ACGIH
		STEL	10 mg/m3 Inhalable fraction, Aerosol only	ACGIH
DIETHYLENE GLYCOL	111-46-6	TWA	10 mg/m3	US WEEL
DISODIUM TETRABORATE	1330-43-4	TWA	1 mg/m3	NIOSH REL
		PEL	5 mg/m3	CAL PEL
		TWA	10 mg/m3	OSHA P0
		TWA	2 mg/m3 Inhalable fraction (Borate)	ACGIH
		STEL	6 mg/m3 Inhalable fraction (Borate)	ACGIH

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an

**SAFETY DATA SHEET**

Revision Date: 08/31/2018

Print Date: 2/17/2020

SDS Number: R0321370

ZEREX™ G05® 50/50 Antifreeze Coolant

Version: 1.4

ZXG05RU2


approved filter.

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

- Hand protection
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.
- Skin and body protection : Wear as appropriate:
Impervious clothing
Safety shoes
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Wear resistant gloves (consult your safety equipment supplier).
- Hygiene measures : Wash hands before breaks and at the end of workday.
When using do not eat or drink.
When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical state : liquid
- Colour : light yellow
- Odour : No data available
- Odour Threshold : No data available
- pH : Average 8.0
- Melting point/freezing point : No data available
- Boiling point/boiling range : 225 °F / 107 °C
(1013.3 hPa)

		Page: 8
SAFETY DATA SHEET		Revision Date: 08/31/2018
		Print Date: 2/17/2020
ZEREX™ G05® 50/50 Antifreeze Coolant		SDS Number: R0321370
ZXG05RU2		Version: 1.4

Flash point	: > 250.0 °F / > 121.1 °C Method: Cleveland open cup
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: 15.3 %(V)
Lower explosion limit	: 1.7 %(V)
Vapour pressure	: 1.800 mmHg (68.00 °F)
Relative vapour density	: > 1.000AIR=1
Relative density	: No data available
Density	: 1.0779 g/cm ³ (15.56 °C)
Solubility(ies)	
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Oxidizing properties	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under recommended storage conditions.
Possibility of hazardous reactions	: Product will not undergo hazardous polymerization.
Conditions to avoid	: excessive heat Exposure to moisture

**SAFETY DATA SHEET**

Revision Date: 08/31/2018

Print Date: 2/17/2020

SDS Number: R0321370

Version: 1.4

ZEREX™ G05® 50/50 Antifreeze Coolant

ZXG05RU2

Incompatible materials : Acids
Aldehydes
Alkali metals
Alkaline earth metals
Bases
iron salts
strong alkalis
Strong oxidizing agents
Sulphur compounds

Hazardous decomposition products : Alcohols
Aldehydes
carbon dioxide and carbon monoxide
ethers
Hydrocarbons
Organic acids
Sodium oxides
ketones

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Harmful if swallowed.

Product:

Acute oral toxicity : Remarks: Ingestion of medications contaminated with diethylene glycol has caused kidney failure and death in humans. Products containing diethylene glycol should be considered toxic by ingestion.

Acute toxicity estimate: 956.37 mg/kg
Method: Calculation method


Acute dermal toxicity : Remarks: Skin absorption of this material (or a component) may be increased through injured skin.

Components:**ETHYLENE GLYCOL:**

Acute oral toxicity : LD0 (Human): estimated 1.56 g/kg

Assessment: The component/mixture is classified as acute oral toxicity, category 4.

Acute inhalation toxicity : LC50 (Rat): 10.9 mg/l

		Page: 10
SAFETY DATA SHEET		Revision Date: 08/31/2018
		Print Date: 2/17/2020
		SDS Number: R0321370
ZEREX™ G05® 50/50 Antifreeze Coolant		Version: 1.4
ZXG05RU2		

Exposure time: 1 h
 Test atmosphere: dust/mist
 Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): 9,530 mg/kg

Acute toxicity (other routes of administration) : LD50 (Rat): 5,010 mg/kg
 Application Route: Intraperitoneal

DIETHYLENE GLYCOL:

Acute oral toxicity : LD50 (Human): Expected 1,120 mg/kg
 Target Organs: Kidney

Acute inhalation toxicity : LC50 (Rat): > 4.6 mg/l
 Exposure time: 4 h
 Test atmosphere: dust/mist
 Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): 13,300 mg/kg

SODIUM BENZOATE:

Acute oral toxicity : LD50 (Rat, male and female): 3,450 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 12.2 mg/l
 Exposure time: 4 h
 Test atmosphere: dust/mist
 Remarks: Information given is based on data obtained from similar substances.

DISODIUM TETRABORATE:

Acute inhalation toxicity : LC50 (Rat): > 2.03 mg/l
 Exposure time: 4 h
 Test atmosphere: dust/mist
 Method: OECD Test Guideline 403
 Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
 Assessment: No adverse effect has been observed in acute dermal toxicity tests.

SODIUM NITRITE:

Acute oral toxicity : LD50 (Rat): 180 mg/kg

Acute inhalation toxicity : LC50 (Rat): 5.5 mg/l
 Exposure time: 4 h
 Test atmosphere: dust/mist

SODIUM NITRATE:

**SAFETY DATA SHEET**

Revision Date: 08/31/2018

Print Date: 2/17/2020

SDS Number: R0321370

ZEREX™ G05® 50/50 Antifreeze Coolant

Version: 1.4

ZXG05RU2

Acute oral toxicity : LD50 (Rat): ca. 3,430 mg/kg
Method: OECD Test Guideline 401

Skin corrosion/irritation

Not classified based on available information.

Components:**ETHYLENE GLYCOL:**

Species : Rabbit
Result : No skin irritation

DIETHYLENE GLYCOL:

Species : Human
Result : Slight, transient irritation

SODIUM BENZOATE:

Assessment : Slight, transient irritation
Result : Slight, transient irritation

DISODIUM TETRABORATE:

Species : Rabbit
Result : No skin irritation

SODIUM NITRITE:

Assessment : No skin irritation
Result : No skin irritation

SODIUM NITRATE:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : Information given is based on data obtained from similar substances.

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks : Unlikely to cause eye irritation or injury.

Components:**ETHYLENE GLYCOL:**


Result : Slight, transient irritation

DIETHYLENE GLYCOL:

Species : Rabbit
Result : Slight, transient irritation

SODIUM BENZOATE:

Species : Rabbit
Result : Irritating to eyes.
Method : OECD Test Guideline 405

		Page: 12
SAFETY DATA SHEET		Revision Date: 08/31/2018
		Print Date: 2/17/2020
ZEREX™ G05@ 50/50 Antifreeze Coolant		SDS Number: R0321370
ZXG05RU2		Version: 1.4

DISODIUM TETRABORATE:

Result : Slight, transient irritation

SODIUM NITRITE:

Result : Irritating to eyes.
 Assessment : Irritating to eyes.

SODIUM NITRATE:

Species : Rabbit
 Result : Irritating to eyes.
 Method : OECD Test Guideline 405

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

ETHYLENE GLYCOL:

Test Type : Maximisation Test
 Species : Guinea pig
 Assessment : Does not cause skin sensitisation.

DIETHYLENE GLYCOL:

Test Type : Maximisation Test
 Species : Guinea pig
 Method : Directive 67/548/EEC, Annex V, B.6.
 Result : Did not cause sensitisation on laboratory animals.

DISODIUM TETRABORATE:

Test Type : Buehler Test
 Species : Guinea pig
 Assessment : Does not cause skin sensitisation.
 Method : OECD Test Guideline 406

Germ cell mutagenicity

Not classified based on available information.

Components:

ETHYLENE GLYCOL:

Genotoxicity in vitro : Test Type: Ames test
 Test system: Salmonella typhimurium
 Metabolic activation: with and without metabolic activation
 Result: negative

DIETHYLENE GLYCOL:

Genotoxicity in vitro : Test Type: Ames test
 Metabolic activation: with and without metabolic activation
 Method: OECD Test Guideline 471
 Result: negative
 GLP: yes



SAFETY DATA SHEET

Revision Date: 08/31/2018

Print Date: 2/17/2020

SDS Number: R0321370

ZEREX™ G05® 50/50 Antifreeze Coolant

Version: 1.4

ZXG05RU2

Test system: Chinese hamster ovary cells
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 479
Result: negative
GLP: yes

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Species: Mouse
Method: OECD Test Guideline 474
Result: negative
GLP: yes

Carcinogenicity
May cause cancer.

IARC Group 2A: Probably carcinogenic to humans
Sodium nitrite Not Assigned
(nitrite (ingested) under conditions that result in endogenous nitrosation)
Group 2A: Probably carcinogenic to humans
Sodium nitrate Not Assigned
(nitrate (ingested) under conditions that result in endogenous nitrosation)

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity
May damage fertility or the unborn child.


Components:
DISODIUM TETRABORATE:
Reproductive toxicity - : Clear evidence of adverse effects on sexual function and
Assessment fertility, and/or on development, based on animal experiments

STOT - single exposure
Not classified based on available information.

STOT - repeated exposure
May cause damage to organs (Kidney, Liver) through prolonged or repeated exposure if swallowed.

Components:
ETHYLENE GLYCOL:
Exposure routes : Ingestion
Target Organs : Kidney, Liver
Assessment : May cause damage to organs through prolonged or repeated exposure.

DIETHYLENE GLYCOL:
Exposure routes : Ingestion
Target Organs : Kidney
Assessment : May cause damage to organs through prolonged or repeated exposure.

		Page: 14
SAFETY DATA SHEET		Revision Date: 08/31/2018
		Print Date: 2/17/2020
		SDS Number: R0321370
ZEREX™ G05® 50/50 Antifreeze Coolant		Version: 1.4
ZXG05RU2		

Aspiration toxicity

Not classified based on available information.

Experience with human exposure

Components:

ETHYLENE GLYCOL:

Ingestion : Target Organs: Kidney

DIETHYLENE GLYCOL:

General Information : Liver
Kidney

Further information

Product:

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Not classified based on available information.

Long-term (chronic) aquatic hazard : Not classified based on available information.

Components:

ETHYLENE GLYCOL:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 27,540 mg/l
Exposure time: 96 h
Test Type: static test

LC50 (Pimephales promelas (fathead minnow)): 8,050 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Test Type: static test

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 6,500 - 13,000 mg/l
End point: Growth inhibition
Exposure time: 7 Days

Toxicity to fish (Chronic toxicity) : NOEC (Pimephales promelas (fathead minnow)): 32,000 mg/l
Exposure time: 7 d

Toxicity to daphnia and other : NOEC (Daphnia magna (Water flea)): 24,000 mg/l

**SAFETY DATA SHEET**

Revision Date: 08/31/2018

Print Date: 2/17/2020

SDS Number: R0321370

Version: 1.4

ZEREX™ G05® 50/50 Antifreeze Coolant


ZXG05RU2

aquatic invertebrates
(Chronic toxicity)

Exposure time: 7 d

DIETHYLENE GLYCOL:Toxicity to daphnia and other
aquatic invertebrates : LC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 24 h
Test Type: static test
Method: DIN 38412**SODIUM BENZOATE:**Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Method: Static
Remarks: MortalityToxicity to daphnia and other
aquatic invertebrates : LC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Method: Static
Remarks: Mortality**DISODIUM TETRABORATE:**Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 79.7 mg/l
Exposure time: 96 h
Remarks: Information refers to the main component.Toxicity to algae : NOEC (Pseudokirchneriella subcapitata (green algae)): 17.5
mg/l
End point: Growth inhibition
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201
Remarks: Information refers to the main component.Toxicity to fish (Chronic
toxicity) : NOEC (Danio rerio (zebra fish)): 5.6 mg/l
Exposure time: 34 d
Test Type: semi-static test
Method: OECD Test Guideline 210
Remarks: Information refers to the main component.**SODIUM NITRITE:**Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2.35 - 3.81
mg/l
Exposure time: 96 h
Test Type: flow-through test

LC50 (Oncorhynchus mykiss (rainbow trout)): 0.54 - 26.3 mg/l
Exposure time: 96 h
Test Type: flow-through test

		Page: 16
SAFETY DATA SHEET		Revision Date: 08/31/2018
		Print Date: 2/17/2020
ZEREX™ G05® 50/50 Antifreeze Coolant		SDS Number: R0321370
ZXG05RU2		Version: 1.4

- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 15.4 mg/l
 Exposure time: 48 h
 Test Type: static test
 Method: OECD Test Guideline 202
- Toxicity to algae : EC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l
 Exposure time: 72 h
 Test Type: Growth inhibition
 Method: OECD Test Guideline 201
- Toxicity to fish (Chronic toxicity) : NOEC (Ictalurus catus (catfish)): 6.16 mg/l
 Exposure time: 31 d
 Test Type: flow-through test
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Aquatic invertebrates): 9.86 mg/l
 Exposure time: 80 d
 Test Type: static test
- Toxicity to bacteria : EC10 (activated sludge): 210 mg/l
 Exposure time: 3 h
 Test Type: Static
 Method: OECD Test Guideline 209
- SODIUM NITRATE:**
 Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 1,355 - 2,063 mg/l
 Exposure time: 96 h
 Method: Static
 Remarks: Mortality
- Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): 3,581 mg/l
 Exposure time: 48 h
 Method: Static
- LC50 (Daphnia magna (Water flea)): 665 mg/l
 Exposure time: 96 h
 Method: Static
- Persistence and degradability**
Components:
ETHYLENE GLYCOL:
 Biodegradability : Result: Readily biodegradable.
 Biodegradation: 90 - 100 %
 Exposure time: 10 d
 Method: OECD Test Guideline 301
- DIETHYLENE GLYCOL:**
 Biodegradability : Result: Readily biodegradable.
 Biodegradation: 70 - 80 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301B



Valvoline

SAFETY DATA SHEET

Revision Date: 08/31/2018

Print Date: 2/17/2020

SDS Number: R0321370

ZEREX™ G05® 50/50 Antifreeze Coolant

Version: 1.4

ZXG05RU2

SODIUM BENZOATE:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 88 %
Exposure time: 28 d
Method: OECD Test Guideline 301

DISODIUM TETRABORATE:

Biodegradability : Result: The methods for determining biodegradability are not applicable to inorganic substances.

SODIUM NITRITE:

Biodegradability : Result: The methods for determining biodegradability are not applicable to inorganic substances.

No data available

Bioaccumulative potential

Components:

ETHYLENE GLYCOL:

Bioaccumulation : Species: Crayfish (Procambarus)
Bioconcentration factor (BCF): 0.27
Exposure time: 61 d
Concentration: 1000 mg/l
Method: Flow through

Partition coefficient: n-octanol/water : log Pow: -1.36

DIETHYLENE GLYCOL:

Bioaccumulation : Species: Leuciscus idus (Golden orfe)
Bioconcentration factor (BCF): 100

Partition coefficient: n-octanol/water : log Pow: -1.47

SODIUM NITRITE:

Partition coefficient: n-octanol/water : log Pow: -3.700 (25 °C)

No data available

Mobility in soil

Components:

SODIUM NITRITE:

Stability in soil : Remarks: Not expected to adsorb on soil.


No data available

Other adverse effects

No data available

Product:

Additional ecological information : No data available

		Page: 18
SAFETY DATA SHEET		Revision Date: 08/31/2018
		Print Date: 2/17/2020
		SDS Number: R0321370
ZEREX™ G05® 50/50 Antifreeze Coolant		Version: 1.4
ZXG05RU2		

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

U.S. DOT - ROAD

Not dangerous goods

CFR_RAIL_C

Not dangerous goods

U.S. DOT - INLAND WATERWAYS


Not dangerous goods

TDG_ROAD_C

Not dangerous goods

TDG_RAIL_C

Not dangerous goods

	Page: 19
	SAFETY DATA SHEET
	Revision Date: 08/31/2018
	Print Date: 2/17/2020
	SDS Number: R0321370
ZEREX™ G05® 50/50 Antifreeze Coolant	Version: 1.4
ZXG05RU2	

TDG_INWT_C

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX_DG

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant		no
------------------	--	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity


Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
ETHYLENE GLYCOL	107-21-1	5000	9914


SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Reproductive toxicity
 Specific target organ toxicity (single or repeated exposure)
 Acute toxicity (any route of exposure)

California Prop. 65

 **WARNING:** Reproductive Harm - www.P65Warnings.ca.gov.

		Page: 20
SAFETY DATA SHEET		Revision Date: 08/31/2018
		Print Date: 2/17/2020
		SDS Number: R0321370
ZEREX™ G05® 50/50 Antifreeze Coolant		Version: 1.4
ZXG05RU2		

The components of this product are reported in the following inventories:

- DSL : All components of this product are on the Canadian DSL
- AICS : On the inventory, or in compliance with the inventory
- ENCS : Not in compliance with the inventory
- KECI : Not in compliance with the inventory
- PICCS : Not in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory
- TSCA : On TSCA Inventory


TSCA list

The following substance(s) is/are subject to TSCA 12(b) export notification requirements:
 SODIUM NITRITE 7632-00-0

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 08/31/2018

<p>NFPA:</p> <div style="text-align: center;">  </div> <p style="text-align: center;">Special hazard.</p>	<p>HMIS III:</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="background-color: #0056b3; color: white; text-align: center;">HEALTH</td> <td style="text-align: center;">1*</td> </tr> <tr> <td style="background-color: #ff0000; color: white; text-align: center;">FLAMMABILITY</td> <td style="text-align: center;">1</td> </tr> <tr> <td style="background-color: #ffff00; text-align: center;">PHYSICAL HAZARD</td> <td style="text-align: center;">0</td> </tr> </table> <p style="font-size: small;">0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	1*	FLAMMABILITY	1	PHYSICAL HAZARD	0
HEALTH	1*						
FLAMMABILITY	1						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification
 Combustible Liquid Class IIIB

Full text of H-Statements

- H272 May intensify fire; oxidizer.
- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H319 Causes serious eye irritation.

**SAFETY DATA SHEET**

Revision Date: 08/31/2018

Print Date: 2/17/2020

SDS Number: R0321370

ZEREX™ G05® 50/50 Antifreeze Coolant

Version: 1.4

ZXG05RU2

H350 May cause cancer.
H360 May damage fertility or the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure if swallowed.


Sources of key data used to compile the Safety Data Sheet
Valvoline internal data including own and sponsored test reports
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists
BEI : Biological Exposure Index
CAS : Chemical Abstracts Service (Division of the American Chemical Society).
CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
FG : Food grade
GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
H-statement : Hazard Statement
IATA : International Air Transport Association.
IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization
ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
IMDG : International Maritime Code for Dangerous Goods
ISO : International Organization for Standardization
logPow : octanol-water partition coefficient
LCxx : Lethal Concentration, for xx percent of test population
LDxx : Lethal Dose, for xx percent of test population.
ICxx : Inhibitory Concentration for xx of a substance
Ecxx : Effective Concentration of xx
N.O.S.: Not Otherwise Specified
OECD : Organization for Economic Co-operation and Development
OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic
PPE : Personal Protective Equipment
STEL : Short-term exposure limit
STOT : Specific Target Organ Toxicity
TLV : Threshold Limit Value

	Page: 22
SAFETY DATA SHEET	Revision Date: 08/31/2018
	Print Date: 2/17/2020
	SDS Number: R0321370
ZEREX™ G05® 50/50 Antifreeze Coolant	Version: 1.4
ZXG05RU2	

TWA : Time-weighted average
vPvB : Very Persistent and Very Bioaccumulative
WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act
DOT : Department of Transportation
FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act
HMIRC : Hazardous Materials Information Review Commission
HMIS : Hazardous Materials Identification System
NFPA : National Fire Protection Association
NIOSH : National Institute for Occupational Safety and Health
OSHA : Occupational Safety and Health Administration
PMRA : Health Canada Pest Management Regulatory Agency
RTK : Right to Know
WHMIS : Workplace Hazardous Materials Information System